



Design & Genius in one

Enhanced aesthetics designed to integrate seamlessly into the ceiling

Designer Comfort



VISTA™ is a remarkable blend of iconic design and engineering excellence with an elegant white or a silver and white finish. Fitting within the ceiling grid and discreetly mounted to the ceiling itself, VISTA™ is stylish, low profile, and compact. High efficiency and comfort is delivered through the combined use of floor and

presence sensors (optional). It is also possible to close individual louvers via the wired remote control for personalized comfort.



Features

- » Seamless integration in standard architectural ceiling tiles, leaving only 5/16"
- » High efficiencies with up to 18.9 SEER and up to 12.5 HSPF
- » Reduced energy consumption thanks to specially developed small tube heat exchanger, DC fan motor and two optional intelligent sensors
- » Remarkable blend of iconic design and engineering excellence with an elegant finish in white or a combination of silver and white
- » No optional adapter needed for DIII-connection, link your unit into the wider building management system
- » Fresh air integration possible
- » 12-Year Parts Limited Warranty*



* Complete warranty details available from your local dealer or at www.daikincomfort.com. To receive the 12-Year Parts Limited Warranty, online registration must be completed within 60 days of installation. Online registration is not required in California or Quebec.

INDOOR VISTA UNIT: FFQ_Q2VJU					
Model Name		FFQ09Q2VJU	FFQ12Q2VJU	FFQ15Q2VJU	FFQ18Q2VJU*
Outdoor Unit Compatibility (Multi-Zone Only)		2MXS18NMVJU	2MXS18NMVJU	2MXS18NMVJU	3MXS24NMVJU 4MXS36NMVJU RMSX48LVJU
		3MXS24NMVJU	3MXS24NMVJU	3MXS24NMVJU	
		4MXS36NMVJU	4MXS36NMVJU	4MXS36NMVJU	
		RMSX48LVJU	RMSX48LVJU	RMSX48LVJU	
		2MXL18QMVJU	2MXL18QMVJU	2MXL18QMVJU	3MXL24QMVJU
		3MXL24QMVJU	3MXL24QMVJU	3MXL24QMVJU	
Cooling Capacity (Nominal) ⁺	BTU/h	Depends on outdoor unit connection			Available Spring 2017
Heating Capacity (Nominal) ⁺					
Power Supply	V/Ph/Hz	208-230/1/60			
Airflow Rate (H/L) - Cooling	cfm (m ³ /min)	378 (10.7) / 268 (7.6)	406 (11.5) / 268 (7.6)	420 (11.9) / 293 (8.3)	
Sound Pressure (H/L)	dB(A)	38.0 / 29.0	39.0 / 30.0	40.0 / 31.0	
Piping Connections	Liquid (O.D.)	Ø 1/4			
	Gas (O.D.)	Ø 3/8 (Ø 9.5)		Ø 1/2 (Ø 12.7)	
	Condensate Drain (O.D.)	Ø 1 1/32 (Ø 26) Ø 25/32 (Ø 20)			
Dimensions (H x W x D)	in. (mm)	10 1/4 x 22 5/8 x 22 5/8 (260 x 575 x 575)			
Net Weight	lbs. (kg)	36 (16)			

*Spring 2017 - check with your distributor for availability



Shown with panel
BYFQ60C2W1W



Shown with panel
BYFQ60C2W1S

Standard Features:

Draft Prevention



This system directs warm air to the floor in winter and cool air across the room in summer for optimal efficiency and comfort. The large flap governs airflow direction while the small flap (or diffuser) swings, producing fine air currents that help circulate the air around the room.

Individual Louver Control



The new louver changes the delivery angle to horizontal for cooling and vertical for heating operation, to keep cold or warm air from blowing directly onto your body.

Included in the optional sensor kit:

Presence and Floor Sensor - optional part #BRYQ60A2(W/S)



The presence and floor sensors are infrared sensors with the ability to sense movement in the room. When you are in the room, the system operates normally. If you leave the room for more than 20 minutes the system automatically changes to an energy-saving operation. Using the intelligent eye, savings of up to 20% in cooling and up to 30% in heating can be achieved. The floor sensor detects the average floor temperature and ensures even temperature distribution between ceiling and floor.



ENERGY STAR® and the ENERGY STAR mark are registered trademarks owned by the U.S. Environmental Protection Agency. ENERGY STAR products are third-party certified by an EPA-recognized Certification Body. Products that earn the ENERGY STAR prevent greenhouse gas emissions by meeting strict energy efficiency guidelines set by the U.S. Environmental Protection Agency.

This Product meets ENERGY STAR requirements when appropriate coil components are used. Ask your contractor for details.

ADDITIONAL INFORMATION

Before purchasing this appliance, read important information about its estimated annual energy consumption, yearly operating cost, or energy efficiency rating that is available from your retailer. Visit www.daikincomfort.com



Our continuing commitment to quality products may mean a change in specifications without notice.

© 2016 DAIKIN NORTH AMERICA LLC · Houston, Texas · USA · www.daikincomfort.com or www.daikinac.com

PF-VISTAMZ 11-16